

## **Deck Above & Goose Neck Trailer**



### **Deck Above and Goose Neck Trailers**

It doesn't take much to see that a deck above or goose neck trailer is built for one thing – work. The massive size and length of these trailers tell you one thing – these trailers mean business and are built for hard work. If you need a trailer that is going to last then you know that you have got to look at a Rainbow trailer today.

#### **The Express**

This is our introductory Deck Over line with the same solid construction found in all trailers.

#### **The Excursion**

This trailer has been built with additional features for those who use their trailer every day. From the family farm to hot shot deliveries to the oil fields of Western Canada these combine the right features and durability to get the job done quickly and easily.

If you have been looking for a bigger deck above or goose neck trailer, then you need not look any further than the Rainbow trailer line. These trailers are 100% Canadian Made at the Rainbow factory in Canada since 1991. When you buy a Rainbow trailer you are not only buying a trailer that will last longer, but you are also buying a trailer that is built tough to do the job. Don't skimp when it comes to buying a quality trailer – buy yours from Rainbow today.

Specifications subject to change without notice

## Standard Features

	<b>EXPRESS</b>	<b>Excursion</b>
	<input type="checkbox"/>	<input type="checkbox"/>
2" painted spruce floor	✓	✓
2 5/16" Ball Coupler	✓	✓
Easy Lube spring axles	✓	✓
Oil Bath spring axles (20,000 lb GVW)	✓	✓
4 Leaf double Eye Suspension	✓	✓
5 Leaf Slipper Suspension (14,000 & 21,000 lb GVWR trailers)	✓	✓
6" Channel Frame & Hitch	✓	✓
12" I-beam frame (All trailers over 20')	✓	✓
Radial Tires	✓	✓
Metal preparation by sandblasting	✓	✓
Metal under deck primed	✗	✓
2 - Part Epoxy primer	✓	✓
High quality black topcoat paint	✓	✓
Stone Guard Protection	✗	✓
Silver Graphics Package	✗	✓
Front Bump rail	✓	✓
Heavy Duty Stake Pockets	✓	✓
5,000 lb Top Wind Jack	✓	✓
12,000 lb Side Wind Jack (14,000 lb GVW and greater)	✗	✓
Safety Chains (Compliant with SAE standards)	✓	✓
DOT Compliant Electric Breakaway kit	✓	✓
DOT Compliant Rubber mounted sealed beam lights	✓	✓
Wiring enclosed in poly conduit	✓	✓
7 Prong RV Plug	✓	✓

## Available Options

★ = Standard Feature

	<b>EXPRESS</b>	<b>Excursion</b>
Axle & Tire Options		
14,000 lb GVWR - Tandem 7,000 lb axles (6" Channel Frame & Hitch)	<input type="checkbox"/>	<input type="checkbox"/>
16,000 lb GVWR - Tandem 8,000 lb axles (12" I-beam Frame & Hitch)	<input type="checkbox"/>	<input type="checkbox"/>
21,000 lb GVWR - Tridem 7000 lb axles	<input type="checkbox"/>	<input type="checkbox"/>

(12" I-beam Frame & Hitch)		
24,000 lb GVWR - Tridem 8,000 lb axles	<input type="checkbox"/>	<input type="checkbox"/>
(12" I-beam Frame & Hitch)		
20,000 lb GVWR - Tandem 10,000 lb axles	<input type="checkbox"/>	<input type="checkbox"/>
(12" I-beam Frame & Hitch)		
24,000 lb GVWR - Tandem 12,000 lb axles	<input type="checkbox"/>	<input type="checkbox"/>
(12" I-beam Frame & Hitch)		
Torflex Axle Upgrade	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Upgrade to G Range 14 Ply Tires (All trailers except 9,900 lb GVW)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spare Tire	<input type="checkbox"/>	<input type="checkbox"/>
Spare Tire Holder	<input type="checkbox"/>	<input type="checkbox"/>
Aluminum Wheel Upgrade	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Coupler Options		
2 5/16" Height Adjustable Coupler	<input type="checkbox"/>	<input type="checkbox"/>
Height Adjustable Pintle Ring	<input type="checkbox"/>	<input type="checkbox"/>
Gooseneck	<input type="checkbox"/>	<input type="checkbox"/>
RV King Pin	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Upgrade to 12K Jack (9,900 lb GVWR trailer)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2nd 12K Jack (14,000 lb GVW trailer)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spring Loaded 12K Jacks	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2 - 12K Two Speed Jacks	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ramp Options		
Straight deck with 8' Slide in Ramps	<input type="checkbox"/>	<input type="checkbox"/>
2' Dovetail with 8' slide in ramps (6" Channel Frame Trailers Only)	<input type="checkbox"/>	<input type="checkbox"/>
2' Dovetail with sliding flip up ramps (6" Channel Frame Trailers Only)	<input type="checkbox"/>	<input type="checkbox"/>
4.5' Dovetail with 8' slide in ramps (12" I-beam Frame Trailers Only)	<input type="checkbox"/>	<input type="checkbox"/>
4.5' Dovetail with sliding flip up ramps (12" I-beam Frame Trailers Only)	<input type="checkbox"/>	<input type="checkbox"/>
4.5' Self Leveling Dove With Channel & Angle Iron Frame (12" I-beam Frame Trailers Only)	<input type="checkbox"/>	<input checked="" type="checkbox"/>
4.5' Self Leveling Dove (Formed Diamond Plate)	<input type="checkbox"/>	<input type="checkbox"/>
3rd Ramp for Self Leveling Dove	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Other Options		
Rubrail	<input type="checkbox"/>	<input type="checkbox"/>
D-rings	<input checked="" type="checkbox"/>	<input type="checkbox"/>

4" Weld on Winches	X	<input type="checkbox"/>
Sliding winch track with 4" sliding winches	X	<input type="checkbox"/>
L.E.D Lights Upgrade	X	<input type="checkbox"/>
Underbody Toolbox	X	<input type="checkbox"/>
Deck Step	X	<input type="checkbox"/>

## Specifications

### Tandem Deck Above Bumper Hitch 6" Channel Frame (9,900 & 14,000 lb GVW)

	Express		
	0516E	0518E	0520E
	Excursion		
	0516M	0518M	0520M
Axle	2-5200 lb	2-5200 lb	2-5200 lb
Overall Length	20' 2"	22' 2"	24' 2"
Deck Length	16'	18'	20'
Deck Height	32"	32"	32"
GAWR	10,400 lb.	10,400 lb.	10,400 lb.
GVWR	9,900 lb.	9,900 lb.	9,900 lb.
Curb Weight	3180 lb.	3362 lb.	3544 lb.
Payload Capacity	7,728 lb.	7,518 lb.	7,309 lb.
Tires	225/75R15D	225/75R15D	225/75R15D
Wheels	6-55 Bolt	6-55 Bolt	6-55 Bolt
Frame	6" C	6" C	6" C
Jack	1-5K	1-5K	1-5K

### Tandem Deck Above Bumper Hitch 6" Channel Frame (9,900 & 14,000 lb GVW)

	Continued		
	Express		
	0716E	0718E	0720E
	Excursion		
	0716M	0718M	0720M
Axle	2-7000 lb	2-7000 lb	2-7000 lb
Overall Length	20' 6"	22' 6"	24' 6"
Deck Length	16'	18'	20'
Deck Height	37"	37"	37"
GAWR	14,000 lb.	14,000 lb.	14,000 lb.
GVWR	14,000 lb.	14,000 lb.	14,000 lb.
Curb Weight	3240 lb.	3422 lb.	3604 lb.
Payload Capacity	12,374 lb	12,164 lb	11,955 lb
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt

Frame	6" C	6" C	6" C
Jack - Express	1-5K	1-5K	1-5K
Jack - Excursion	1-12K	1-12K	1-12K

**Tandem Deck Above Bumper Hitch 12" I-Beam Frame (14,000 lb GVW)**

		<b>Express</b>	
	0722E	0724E	0726E
		<b>Excursion</b>	
	0722M	0724M	0726M
Axle	2-7000 lb	2-7000 lb	2-7000 lb
Overall Length	26' 6"	28' 6"	30' 6"
Deck Length	22'	24'	26'
Deck Height	37"	37"	37"
GAWR	14,000 lb.	14,000 lb.	14,000 lb.
GVWR	14,000 lb.	14,000 lb.	14,000 lb.
Curb Weight	3786 lb.	3968 lb.	4150 lb.
Payload Capacity	11,746 lb	11,536 lb	9,998 lb
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam
Jack	1-12K	1-12K	1-12K

**Tridem Deck Above Bumper Hitch 12" I-Beam Frame (21,000 lb GVW)**

		<b>Express</b>		
	07324E	07326E	07328E	07330E
		<b>Excursion</b>		
	07324M	07326M	07328M	07330M
Axle	3- 7000 lb	3- 7000 lb	3- 7000 lb	3- 7000 lb
Overall Length	28' 6"	30' 6"	32' 6"	34' 6"
Deck Length	24'	26'	28'	30'
Deck Height	37"	37"	37"	37"
GAWR	21,000 lb.	21,000 lb.	21,000 lb.	21,000 lb.
GVWR	21,000 lb	21,000 lb	21,000 lb	21,000 lb
Curb Weight	4407 lb.	4589 lb.	4771 lb.	4953 lb.
Payload Capacity	19,081 lb	18,872 lb	18,663 lb	18,454 lb
Tires	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K

**Tandem Dual Deck Above Bumper Hitch 12" I-beam Frame (20,000 lb GVW)**

		<b>Express</b>	
	O1026E	O1028E	O1030E
		<b>Excursion</b>	
	O1026M	O1028M	O1030M
Axle	2-10,000 lb	2-10,000 lb	2-10,000 lb

Overall Length	30' 6"	32' 6"	34' 6"
Deck Length	26'	28'	30'
Deck Height	38.5"	38.5"	38.5"
GAWR	20,000 lb.	20,000 lb.	20,000 lb.
GVWR	20,000 lb.	20,000 lb.	20,000 lb.
Curb Weight	4971 lb.	5153 lb.	5335 lb.
Payload Capacity	17,283 lb.	17,074 lb.	16,864 lb.
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K

**Tandem Deck Above Gooseneck 6" Channel Frame (14,000 lb GVW)**

**Express**

0G716E                      0G718E                      0G720E

**Excursion**

0G716M                      0G718M                      0G720M

Axle	2-7000 lb	2-7000 lb	2-7000 lb
Overall Length	24' 10"	26' 10"	28' 10"
Deck Length	16'	18'	20'
Deck Height	37"	37"	37"
GAWR	14,000 lb.	14,000 lb.	14,000 lb.
GVWR	14,000 lb	14,000 lb	14,000 lb
Curb Weight	3423 lb.	3653 lb.	3883 lb.
Payload Capacity	12,692 lb	12,416 lb	12,140 lb
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	6" C	6" C	6" C
Jack	1-12K	1-12K	1-12K

**Tandem Deck Above Gooseneck 12" I-Beam Frame (14,000 lb GVW)**

**Express**

OG722E                      OG724E                      OG726E

**Excursion**

OG722M                      OG724M                      OG726M

Axle	2-7000 lb	2-7000 lb	2-7000 lb
Overall Length	30' 10"	32' 10"	34' 10"
Deck Length	22'	24'	26'
Deck Height	37"	37"	37"
GAWR	14,000 lb.	14,000 lb.	14,000 lb.
GVWR	14,000 lb	14,000 lb	14,000 lb
Curb Weight	4113 lb.	4343 lb.	4573 lb.
Payload Capacity	11,864 lb	11,588 lb	11,312 lb
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam

Jack 1-12K 1-12K 1-12K

**Tandem Deck Above Gooseneck 12" I-Beam Frame (16,000 lb GVW)**

	<b>Express</b>				
	OG822E	OG824E	OG826E	OG828E	OG830E
	<b>Excursion</b>				
	OG822M	OG824M	OG826M	OG828M	OG830M
Axle	2-8000 lb	2-8000 lb	2-8000 lb	2-8000 lb	2-8000 lb
Overall Length	30' 10"	32' 10"	34' 10"	36' 10"	38' 10"
Deck Length	22'	24'	26'	28'	30'
Deck Height	37"	37"	37"	37"	37"
GAWR	16,000 lb.	16,000 lb.	16,000 lb.	16,000 lb.	16,000 lb.
GVWR	16,000 lb.	16,000 lb.	16,000 lb.	16,000 lb.	16,000 lb.
Curb Weight	4513 lb.	4743 lb.	4973 lb.	5203 lb.	5433 lb.
Payload Capacity	13,210 lb	12,945 lb	12,681 lb	12,416 lb	12,152 lb
Tires	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	1-12K	1-12K	1-12K	1-12K	1-12K

**Tridem Deck Above Gooseneck 12" I-Beam Frame (21,000 lb GVW)**

	<b>Express</b>				
	OG7320E	OG7322E	OG7324E	OG7326E	OG7328E
	<b>Excursion</b>				
	OG7320M	OG7322M	OG7324M	OG7326M	OG7328M
Axle	3- 7000 lb	3- 7000 lb	3- 7000 lb	3- 7000 lb	3- 7000 lb
Overall Length	28' 10"	30' 10"	32' 10"	34' 10"	36' 10"
Deck Length	20'	22'	24'	26'	28'
Deck Height	37"	37"	37"	37"	37"
GAWR	21,000 lb.	21,000 lb.	21,000 lb.	21,000 lb.	21,000 lb.
GVWR	21,000 lb	21,000 lb	21,000 lb	21,000 lb	21,000 lb
Curb Weight	4158 lb.	4378 lb.	4598 lb.	4818 lb.	5038 lb.
Payload Capacity	20,210 lb	19,946 lb	19,682 lb	19,418 lb	19,154 lb
Tires	235/80R16E	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K	2-12K

**Tridem Deck Above Gooseneck 12" I-Beam Frame (21,000 lb GVW) Continued**

	<b>Express</b>			
	OG7330E	OG7332E	OG7334E	OG7336E
	<b>Excursion</b>			
	OG7330M	OG7332M	OG7334M	OG7336M
Axle	3- 7000 lb	3- 7000 lb	3- 7000 lb	3- 7000 lb
Overall Length	38' 10"	40' 10"	42' 10"	44' 10"
Deck Length	30'	32'	34'	36'

Deck Height	37"	37"	37"	37"
GAWR	21,000 lb.	21,000 lb.	21,000 lb.	21,000 lb.
GVWR	21,000 lb	21,000 lb	21,000 lb	21,000 lb
Curb Weight	5258 lb.	5478 lb.	5698 lb.	5918 lb.
Payload Capacity	18,890 lb	18,626 lb	18,362 lb	18,098 lb
Tires	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K

**Tridem Deck Above Gooseneck 12" I-Beam Frame (24,000 lb GVW)**

	<b>Express</b>				
	OG8320E	OG8322E	OG8324E	OG8326E	OG8328E
	<b>Excursion</b>				
	OG8320M	OG8322M	OG8324M	OG8326M	OG8328M
Axle	3- 8000 lb	3- 8000 lb	3- 8000 lb	3- 8000 lb	3- 8000 lb
Overall Length	28' 10"	30' 10"	32' 10"	34' 10"	36' 10"
Deck Length	20'	22'	24'	26'	28'
Deck Height	37"	37"	37"	37"	
GAWR	24,000 lb.	24,000 lb.	24,000 lb.	24,000 lb.	24,000 lb.
GVWR	24,000 lb	24,000 lb	24,000 lb	24,000 lb	24,000 lb
Curb Weight	4758 lb.	4978 lb.	5198 lb.	5418 lb.	5638 lb.
Payload Capacity	22,128 lb	21,875 lb	21,622 lb	21,363 lb	21,116 lb
Tires	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K	2-12K

**Tridem Deck Above Gooseneck 12" I-Beam Frame (24,000 lb GVW) Continued**

	<b>Express</b>			
	OG8330E	OG8332E	OG8334E	OG8336E
	<b>Excursion</b>			
	OG8330M	OG8332M	OG8334M	OG8336M
Axle	3- 8000 lb	3- 8000 lb	3- 8000 lb	3- 8000 lb
Overall Length	38' 10"	40' 10"	42' 10"	44' 10"
Deck Length	30'	32'	34'	36'
Deck Height	37"	37"	37"	37"
GAWR	24,000 lb.	24,000 lb.	24,000 lb.	24,000 lb.
GVWR	24,000 lb	24,000 lb	24,000 lb	24,000 lb
Curb Weight	5858 lb.	6078 lb.	6298 lb.	6518 lb.
Payload Capacity	21,863 lb	20,610 lb	20,357 lb	20,104 lb
Tires	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K



**Tandem Dual Deck Above Gooseneck 12" I-beam Frame (20,000 lb GVW)**

	<b>Express</b>			
	OG1024E	OG1026E	OG1028E	OG1030E
	<b>Excursion</b>			
	OG1024M	OG1026M	OG1028M	OG1030M
Axle	2-10,000 lb	2-10,000 lb	2-10,000 lb	2-10,000 lb
Overall Length	32' 10"	34' 10"	36' 10"	38' 10"
Deck Length	24'	26'	28'	30'
Deck Height	38.5"	38.5"	38.5"	38.5"
GAWR	20,000 lb.	20,000 lb.	20,000 lb.	20,000 lb.
GVWR	20,000 lb.	20,000 lb.	20,000 lb.	20,000 lb.
Curb Weight	5134 lb.	5364 lb.	5594 lb.	5824 lb.
Payload Capacity	17,839 lb.	17,563 lb.	17,287 lb.	17,011 lb.
Tires	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K

**Tandem Dual Deck Above Gooseneck 12" I-beam Frame (20,000 lb GVW)**

	<b>Continued</b>		
	<b>Express</b>		
	OG1032E	OG1034E	OG1036E
	<b>Excursion</b>		
	OG1032M	OG1034M	OG1036M
Axle	2-10,000 lb	2-10,000 lb	2-10,000 lb
Overall Length	40' 10"	42' 10"	44' 10"
Deck Length	32'	34'	36'
Deck Height	38.5"	38.5"	38.5"
GAWR	20,000 lb.	20,000 lb.	20,000 lb.
GVWR	20,000 lb.	20,000 lb.	20,000 lb.
Curb Weight	6054 lb.	6284 lb.	6514 lb.
Payload Capacity	16,735 lb.	16,459 lb.	16,183 lb.
Tires	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K

**Tandem Dual Deck Above Gooseneck 12" I-beam Frame (24,000 lb GVW)**

	<b>Express</b>			
	OG1230E	OG1232E	OG1234E	OG1236E
	<b>Excursion</b>			
	OG1230M	OG1232M	OG1234M	OG1236M
Axle	2-12,000 lb	2-12,000 lb	2-12,000 lb	2-12,000 lb
Overall Length	38' 10"	40' 10"	42' 10"	44' 10"
Deck Length	30'	32'	34'	36'
Deck Height	38.5"	38.5"	38.5"	38.5"

GAWR	24,000 lb.	24,000 lb.	24,000 lb.	24,000 lb.
GVWR	24,000 lb.	24,000 lb.	24,000 lb.	24,000 lb.
Curb Weight	5940 lb.	6170 lb.	6400 lb.	6630 lb.
Payload Capacity	20,769 lb.	20,504 lb.	20,240 lb.	19,975 lb.
Tires	235/80R16E	235/80R16E	235/80R16E	235/80R16E
Wheels	8-65 Bolt	8-65 Bolt	8-65 Bolt	8-65 Bolt
Frame	12" I Beam	12" I Beam	12" I Beam	12" I Beam
Jack	2-12K	2-12K	2-12K	2-12K